



G. D. KOUTLIS S.A.

MANUFACTURERS OF PAINTS & VARNISHES

FACTORY: 34th km ATHENS/LAMIA NATIONAL ROAD

(OROPOS/MARCOPOULO CROSSING),

GR-19011 POLYDENDRI ATTIKIS , GREECE.

PHONES: +30-22950-22146 (5 lines) / FAX : +30-22950-22124

<http://www.erlac.gr>, e-mail: support@erlac.gr – exports@erlac.gr

SMART – PLAST

GENERAL CHARACTERISTICS

Water-Dispersion paint, based on water-diluted polymer, suitable for coating and protection of indoor/outdoor building surfaces.

It provides very good adhesion and elasticity, high washing resistance and outstanding whiteness and coverage.

APPLICATION

Application surfaces : Clean, dry, old and new plasters, concrete, cement, gypsumboard et.c.

Pre-treatment: As an undercoat, apply TOP PRIMER or MONODUR Insulator diluted 40% with WS-100, or the same SMART – PLAST paint diluted with water at 40%.

Application: With roller, brush or gun diluted with water at 10-20%, on very well cleaned surfaces.

Avoid application when environment temperature is less than 5° Celsius or higher than 40° Celsius.

The product is subject to directive 2004/42/E.C.

Category A/a “Interior matt walls and ceilings. – Type waterbased”.

Limit V.O.C. value : 75 gr/lit (2007), 30 gr/lit (2010).

V.O.C. maximum for this product ready for use : 29gr/lit.

TECHNICAL CHARAKTERISTICS

COLOUR: *White*

SPECIFIC GRAVITY: *1.50 – 1.60g/ml*

VISCOSITY: *8000-9000 cP*

GLOSS: *Mat*

THINNING: *5-10% with water*

DRYING TIME: *1 - 2h*

RECOATING: *2-4h*

THEORETICAL COVERAGE: *10m²/lt*

PACKING: *1lt, 3 lt, 10lt*