

# **G. D. KOUTLIS S.A.**

**MANUFACTURERS OF PAINTS, VARNISHES & SYNTHETIC RESINS**

**FOR BUILDINGS, INDUSTRY, CARS, FURNITURE & HOUSEHOLD USE.**

**MAIL ADDRESS :** 34<sup>th</sup> km ATHENS-LAMIA NATIONAL ROAD, GR-19011 AVLONA  
ATTIKIS , GREECE.

**PHONES :** +30-295-22146 **FAX :** +30-295-22124 **E-MAIL :** support@erlac.gr

---



## **STOCOFIN**

### **GENERAL CHARACTERISTICS**

Water-soluble, acrylic stucco, for indoor/outdoor surfaces from concrete, plaster, cement, gypsumboard, e.t.c..  
It covers easily all the defects, corners, joints of building surfaces, novopan, wood e.t.c..  
Applies easily and softly. Dries quickly and sands easily.

### **APPLICATION**

Stir well without diluting and apply on dry and well cleaned surfaces. Do not mix Stocofin with any other material. Great thinning must be avoided, because causes lower and poor covering ability. Apply with spatula or sponge. After drying the first layer, apply a second, if needed. When Stocofin dry, sand with sandpaper No 120 and apply MONODUR primer, before the application of the final coat.

### **TECHNICAL DATA**

**Color:** White.  
**Specific Gravity:** 1,70-1,75 gr/ml.  
**Thinning:** With water if needed.  
**Drying Time:** 1-2 hours.  
**Sanding Time:** 2-3 hours.  
**Recoatable:** 2-4 hours.  
**Packing:** 0.4, 0.8, 5 kg.

**Does not raise in Law 2004/42/EC**