



G. D. KOUTLIS S.A.

MANUFACTURERS OF PAINTS & VARNISHES

FACTORY: 34th km ATHENS/LAMIA NATIONAL ROAD

(OROPOS/MARCOPOULO CROSSING),

GR-19011 POLYDENDRI ATTIKIS , GREECE.

PHONES: +30-22950-22146 (5 lines) / **FAX :** +30-22950-22124

<http://www.erlac.gr>, **e-mail:** support@erlac.gr – exports@erlac.gr

TOP PRIMER

GENERAL CHARACTERISTICS

Water-diluted, acrylic-based primer, suitable for all surfaces and all paints. It provides excellent resistance on alkalic surfaces such as cement, concrete, etc. It has very good adhesion in all the building surfaces, protects from humidity and displays excellent resistances to weather conditions.

APPLICATION

Surfaces to apply: All the surfaces that will be covered with emulsion or acrylic paint or Relief.

Application: Applies with roller or brush diluted up to 1:4 with water on very well cleaned surfaces.

Avoid application when environmental temperature is less than 5°C or higher than 40°C.

The product is subject to directive 2004/42/E.C.

Category A/g “Primers – Type water based”.

Limit V.O.C. value : 50 gr/lt (2007), 30 gr/lt (2010).

V.O.C. maximum for this product ready for use : 28gr/lt.

TECHNICAL DATA

Color: Colourless.

Specific Gravity: 1,00-1,05 gr/ml.

Thinning: Up to 1 part TOP PRIMER with 4 parts Water.

Drying Time: About 1 hour

Recoatable: 2,5-3 hours.

Theoretical coverage: 30-40 m²/kg.

Packing: 1lt, 3lt, 10 lt.